

Portable Cased, Single Phase — 120 Input, 0-132, 0-140 & 0-280V Output



3PN221B,
3PN501B



1000/1200
Series



1500/2500
Series



3PN2210B

Part No.	Input		Output			Features	Net Wt. LBS.
	Volts	Hertz*	Volts	Constant Current Load			
				Max Amps	Max KVA		
120V Input models with case, cord, plug, receptacle, lighted switch & fuse							
3PN221B	120	60	0-132	2.5	0.33		3
3PN1020B-MOD	120	50/60	0-280	3.5-1.5#	0.42		10.25
3PN1020BV-MOD	120	50/60	0-280	3.5-1.5#	0.42	Analog Voltmeter (+/- 5.0%)	10.25
3PN1020BA-MOD	120	50/60	0-280	3.5-1.5#	0.42	Analog Ammeter (+/- 5.0%)	10.25
3PN501B	120	50/60	0-140	5.0	0.70		7.75
3PN1520B-MOD	120	50/60	0-280	9.5-4.1#	1.14		22
3PN1520B-XDVM	120	50/60	0-280	9.5-4.1#	1.14	Digital Voltmeter (+/- 0.5%)	22
3PN1520BV-MOD	120	50/60	0-280	9.5-4.1#	1.14	Analog Voltmeter (+/- 5.0%)	22
3PN1520BA-MOD	120	50/60	0-280	9.5-4.1#	1.14	Analog Ammeter (+/- 5.0%)	22
3PN1010B	120	50/60	0-140	10.0	1.40		10.25
3PN1010BV	120	50/60	0-140	10.0	1.40	Analog Voltmeter (+/- 5.0%)	10.25
3PN1010BA	120	50/60	0-140	10.0	1.40	Analog Ammeter (+/- 5.0%)	10.25
3PN2520B-MOD	120	50/60	0-280	10-4.4#	1.20		24.25
3PN2520B-XDVM	120	50/60	0-280	10-4.4#	1.20	Digital Voltmeter (+/- 0.5%)	24.25
3PN1210B	120	60	0-120	12.0	1.44		10.25
3PN1510B	120	50/60	0-140	15.0	2.10		18
3PN1510B-DVM	120	50/60	0-140	15.0	2.10	Digital Voltmeter (+/- 0.5%)	18
3PN1510BV	120	50/60	0-140	15.0	2.10	Analog Voltmeter (+/- 5.0%)	18
3PN1510BA	120	50/60	0-140	15.0	2.10	Analog Ammeter (+/- 5.0%)	18
3PN2210B	120	50/60	0-140	22.0	3.08		24.25

Portable Cased, Single Phase — 240 Input, 0-280V Output



Part No.	Input		Output			Features	Net Wt. LBS.
	Volts	Hertz*	Volts	Constant Current Load			
				Max Amps	Max KVA		
240V Input models with case, cord, plug, receptacle, lighted switch & fuse							
3PN1020B	240	50/60	0-280	3.5	0.98		10.25
3PN1020BV	240	50/60	0-280	3.5	0.98	Analog Voltmeter (+/- 5.0%)	10.25
3PN1020BA	240	50/60	0-280	3.5	0.98	Analog Ammeter (+/- 5.0%)	10.25
3PN1220B	240	60	0-240	5.0	1.20		10.25
3PN1520B	240	50/60	0-280	9.5	2.66		22
3PN1520B-DVM	240	50/60	0-280	9.5	2.66	Digital Voltmeter (+/- 0.5%)	22
3PN1520BV	240	50/60	0-280	9.5	2.66	Analog Voltmeter (+/- 5.0%)	22
3PN1520BA	240	50/60	0-280	9.5	2.66	Analog Ammeter (+/- 5.0%)	22
3PN2520B	240	50/60	0-280	10	2.80		24.25
3PN2520B-DVM	240	50/60	0-280	10	2.80	Digital Voltmeter (+/- 0.5%)	24.25



ISE, Inc.

10100 Royalton Rd. - Cleveland, OH 44133
Tel: (440) 237-3200 - Fax: (440) 237-1744

<http://VariableTransformer.com>