



SPECIFICATIONS					
WIRING	INPUT		OUTPUT		
	VOLTS	HERTZ	VOLTS	CONSTANT CURRENT LOAD	
SINGLE PHASE	120	60	0-120	MAX. AMPS	MAX. KVA
				12	1.44

UNLESS OTHERWISE SPECIFIED, TOLERANCE IS # DECIMALS .XX .0000 .06 .0002 .01 1° 1-1/2° UNITS IN [mm] MATERIAL: ALL DIMENSIONS APPLY AFTER PLATING

THE INFORMATION AND DESIGN DISCLOSED HEREIN WAS ORIGINATED BY AND IS THE PROPERTY OF STACO ENERGY PRODUCTS CO., WHICH RESERVES ALL PATENT, PROPRIETARY, DESIGN, MANUFACTURING, REPRODUCTION, USE AND SALE RIGHTS THEREIN, AND TO ANY ARTICLE DISCLOSED THEREIN EXCEPT TO THE EXTENT RIGHTS ARE EXPRESSLY GRANTED TO OTHERS. THE FOREGOING DOES NOT APPLY TO VENDOR PROPRIETARY PARTS.

TITLE: SPEC. CONTROL DRAWING VARIABLE TRANSFORMER MODEL: 3PN1210B

DRAWN BY: S.A. SMITH	DATE: 10/11/96	FIRST USED ON: 3PN1210B	DO NOT SCALE DWG.	CUSTOMER APPROVAL: _____	DATE: _____
CHECKER: _____	DATE: _____	WEIGHT APPROX.: 10.25 LBS	CODE IDENT. NO.: 83008	DWG. SIZE: D	DWG. NO.: 031-2995
ENGINEER: _____	DATE: _____	SCALE: 1=1	SHEET 1 OF 1		

STACO
 ENERGY PRODUCTS CO.
 A COMPONENTS CORPORATION OF AMERICA COMPANY
 DAYTON, OHIO U.S.A.