



SPECIFICATIONS					
WIRING	INPUT		OUTPUT		
	VOLTS	HERTZ	VOLTS	CONSTANT CURRENT LOAD	
SINGLE PHASE	240	50/60	0-280	MAX. AMPS	MAX. KVA
				9.5	2.66

UNLESS OTHERWISE SPECIFIED, TOLERANCE IS #		UNITS		TITLE: SPEC. CONTROL DRAWING			
DECIMALS	HOLES	IN	MM	SPEC. CONTROL DRAWING			
.XX	.06	1-1/2"		DRAWN BY: S.A. SMITH		DATE: 5/17/96	FIRST USED ON: 3PN1520B
.XXX	.005	1°		CHECKER:		DATE:	WEIGHT APPROX.: 22 LBS
MATERIAL:		ALL DIMENSIONS APPLY AFTER PLATING		ENGINEER:		DATE:	SCALE: 1=1
The information and design disclosed herein was originated by and is the property of STACO ENERGY PRODUCTS CO., which reserves all patent, proprietary, design, manufacturing, reproduction, use and sale rights thereto, and to any article disclosed therein except to the extent rights are expressly granted to others. The foregoing does not apply to vendor proprietary parts.				DO NOT SCALE DWG.		CUSTOMER APPROVAL: DATE:	
				CODE IDENT. NO. 83008		DWG. NO. 031-3945	
				SHEET 1 OF 1			