



SPECIFICATIONS											
WIRING	INPUT		OUTPUT				SHAFT ROTATION TO INCREASE VOLTAGE	TERMINAL CONNECTIONS			
	VOLTS	HERTZ	VOLTS	CONSTANT CURRENT LOAD		CONSTANT IMPEDANCE LOAD		FOR INCREASING VOLTAGE AS VIEWED FROM BASE END			
				MAX. AMPS	MAX. KVA	MAX. AMPS	MAX. KVA		INPUT	JUMPER	OUTPUT
SINGLE PHASE	240	60	0-240	5.0	1.20	7.0	1.68	CW	1-4	—	4-3
								CCW	1-4	—	1-3

UNLESS OTHERWISE SPECIFIED, TOLERANCE IS #				UNITS		TITLE: SPEC. CONTROL DRAWING					
DECIMALS	Holes	ANGLES	DRAFT	IN	MM	SPEC. CONTROL DRAWING					
.XX	.0005	.002	1°	1-1/2°		VARIABLE TRANSFORMER					
MATERIAL:				ALL DIMENSIONS APPLY AFTER PLATING		MODEL: 1220B					
DRAWN BY		DATE	FIRST USED ON	DO NOT SCALE DWG.		CUSTOMER APPROVAL		DATE			
S.A. SMITH		9/25/97									
CHECKER	DATE	WEIGHT APPROX.	CODE IDENT. NO.	DWG. NO.							
		9 LBS	83008	031-3260							
ENGINEER	DATE	SCALE	SHEET	DWG. NO.							
		1=1	1 OF 1	031-3260							