



SPECIFICATIONS								
WIRING	INPUT		OUTPUT			SHAFT ROTATION FOR VOLTAGE INCREASE	TERMINAL CONNECTIONS FOR INCREASING VOLTAGE AS VIEWED FROM TOP	
	VOLTS	HERTZ	VOLTS	CONSTANT CURRENT LOAD			INPUT	OUTPUT
THREE PHASE WYE	240	60	0-280	MAX. AMPS	MAX. KVA	CW	2-2-2	3-3-3
				50	24.2			
UNLESS OTHERWISE SPECIFIED, TOLERANCE IS # DECIMALS .XX .0000 .12 .0008 .03 1° 1-1/2°			UNITS IN [mm]		TITLE: SPECIFICATION CONTROL DRAWING VARIABLE TRANSFORMER 5011E-3Y			
MATERIAL:			ALL DIMENSIONS APPLY AFTER PLATING					
DRAWN BY F. SEALE		DATE 3/7/96	FIRST USED ON 5011E-3Y	DO NOT SCALE DWG.	CUSTOMER APPROVAL DATE			
CHECKER		DATE	WEIGHT APPROX.	CODE IDENT. NO. 83008	DWG. SIZE D	DWG. NO. 031-6742		
ENGINEER		DATE	SCALE .25=1	SHEET 1 OF 1				