

(4) HOLES FOR 1/2" DIA. MTG. BOLTS ON 10.75 X 8.25 CENTERS BOTTOM MTG. CHANNEL

Go to [VARIAC.com](http://VARIAC.com) to purchase and for technical support.  
 Made in the USA





FIGURE A  
 MAXIMUM OUTPUT CURRENT OF ANY DUAL INPUT VOLTAGE OR VOLTAGE DOUBLER UNIT OPERATED AT LOWER INPUT VOLTAGE.



SCHEMATIC

\* MAXIMUM OUTPUT CURRENT IN OUTPUT VOLTAGE RANGE FROM 0 TO 25 PERCENT ABOVE LINE VOLTAGE. AT HIGHER OUTPUT VOLTAGES, OUTPUT CURRENT MUST BE REDUCED ACCORDING TO RATING CURVE (SEE FIGURE A).

\*\* MAXIMUM KVA AT MAXIMUM OUTPUT AND CORRESPONDING DE-RATED CURRENT. MAXIMUM KVA AT LOWER OUTPUT VOLTAGES MAY BE CALCULATED FROM RATING CURVE (SEE FIGURE A).

V.D. = VOLTAGE DOUBLER.

SPECIFICATIONS									
WIRING	INPUT		OUTPUT			SHAFT ROTATION FOR INCREASE VOLTAGE	TERMINAL CONNECTIONS		
	VOLTS	HERTZ	VOLTS	CONSTANT CURRENT LOAD			FOR INCREASING VOLTAGE AS VIEWED FROM ROTOR END		
THREE PHASE WYE	480	50/60	0-480	105	87.2	CW	4-4-4	—	D-D-D
		60	0-560	105	101.7		2-2-2	—	D-D-D
	240	60	0-560	* 105-45 V.D.	** 43.6	CW	5-5-5	—	D-D-D

UNLESS OTHERWISE SPECIFIED, TOLERANCE IS #		UNITS		TITLE:		DRAWN BY		DATE		FIRST USED ON		DO NOT SCALE DWG.		CUSTOMER APPROVAL		DATE			
DECIMALS	HOLE	ANGLES	DRAFT	IN	MM	SPEC. CONTROL DWG. MOTORIZED VARIABLE XFMR TYPE: 6020-9Y										DRAWN BY		DATE	
.XX	.12	1°	1-1/2°													TIM RAU		9/23/96	
MATERIAL:				ALL DIMENSIONS APPLY AFTER PLATING		CHECKER		DATE		WEIGHT APPROX.		CODE IDENT. NO.		DWG. SIZE		DWG. NO.			
												.25=1		SHEET 1 OF 1		D 032-8207			

